

Federal Highway Administration, DOT

§ 635.501

pipes, and (2) the number and types of such alternatives which must be set forth in the specifications for various types of drainage installations.

(e) Reference in specifications and on plans to single trade name materials will not be approved on Federal-aid contracts.

§ 635.413 Warranty clauses.

The SHA may include warranty provisions in National Highway System (NHS) construction contracts in accordance with the following:

(a) Warranty provisions shall be for a specific construction product or feature. Items of maintenance not eligible for Federal participation shall not be covered.

(b) All warranty requirements and subsequent revisions shall be submitted to the Division Administrator for advance approval.

(c) No warranty requirement shall be approved which, in the judgment of the Division Administrator, may place an undue obligation on the contractor for items over which the contractor has no control.

(d) A SHA may follow its own procedures regarding the inclusion of war-

ranty provisions in non-NHS Federal-aid contracts.

[60 FR 44274, Aug. 25, 1995]

§ 635.417 Convict produced materials.

(a) Materials produced after July 1, 1991, by convict labor may only be incorporated in a Federal-aid highway construction project if such materials have been:

(1) Produced by convicts who are on parole, supervised release, or probation from a prison or

(2) Produced in a qualified prison facility and the cumulative annual production amount of such materials for use in Federal-aid highway construction does not exceed the amount of such materials produced in such facility for use in Federal-aid highway construction during the 12-month period ending July 1, 1987.

(b) *Qualified prison facility* means any prison facility in which convicts, during the 12-month period ending July 1, 1987, produced materials for use in Federal-aid highway construction projects.

[53 FR 1923, Jan. 25, 1988, as amended at 58 FR 38975, July 21, 1993]

APPENDIX A TO SUBPART D—SUMMARY OF ACCEPTABLE CRITERIA FOR SPECIFYING TYPES OF CULVERT PIPES

Type of drainage installation	Alternatives required			AASHTO designations to be included with alternatives	Application	Remarks
	Yes	No	Number			
Cross drains under high-type pavement. ¹	X	Statewide	Any AASHTO-approved material. ² Do. ²
Other cross-drain installations.	X	3 minimum	M-170 and M-190.do	
Side-drain installations	Xdo	M-36do	Do. ² Specified to meet special conditions. Specified to meet site requirements.
Special installation conditions.	X	Individual installation.	
Special drainage systems (storm sewers, inverted siphons, etc.).	Xdo	

¹ High-type pavement is generally described as FHWA construction type codes I, J, K, L, and plant mix and penetration macadam segments, respectively shown in the right-hand columns of type codes G and H having a combined thickness of surface and base of 7 in or more (or equivalent) or that are constructed on rigid bases.

² Types not included in currently approved AASHTO specifications may be specified if recommended by the State with adequate justification and approved by FHWA.

Subpart E—Interstate Maintenance Guidelines

SOURCE: 45 FR 20793, Mar. 31, 1980, unless otherwise noted.

§ 635.501 Purpose.

To prescribe Interstate maintenance guidelines and establish the policy and procedures to insure that the condition of Interstate routes is maintained at